



Titebond Painter's Caulk

Titebond® Painter's Caulk is an economical, easy-to-use caulk that is formulated for interior pre-paint preparation. It offers good weather-resistance and provides a strong bond to most common building materials, including wood, metal, glass, masonry, aluminum and brick. It can be used for sealing joints, repairing cracks and back-filling gaps.

Titebond Painter's is de-aired for a smooth, uniform bead that extrudes and tools easily. It is intended for interior use and can be painted with a water-based interior paint with one coat and will not bleed through the paint. Titebond Painters is a non-stringing formula that won't sag or drool and it has excellent bead cut-off. It also cleans up with soap and water when wet.

Specifications

- Meets ASTM C-834 Type OP Grade -18°C.

Revised October 2013



Product Features

- Fills gaps, seals joints and repairs cracks
- Paints easily with one coat
- Dries quickly & provides a tight seal
- Uncured material cleans up with soap and water
- Minimal odor
- De-aired for a smoother bead
- Mildew resistant

Physical Properties

Type Latex	Non-reactive VOC 23 g/L (<1.5%)
Color White	Weight/gallon 13.5 lbs.
Solids 82%	Flashpoint None
Viscosity 600,000 cps	Storage life 24 months in tightly closed containers at 50°F to 80°F.
Freeze/thaw stability Stable	

Coverage (maximum): Approximate length of bead according to bead diameter:

Container	1/4" bead	3/8" bead	1/2" bead
10.1 oz. Cartridge	31 ft.	14 ft.	8 ft.

Application Guidelines

Application Temperature Above 40°F. and below 120°F.

Service Temperature Range -25°F. to 180°F.

Method of Application Cartridge/caulking gun

Working Time Approximately 10-15 minutes for 1/4" bead

Working Surfaces Surfaces must be cleaned down to the original substrate, dry and free from oil, grease, water, dirt or any other material that may prevent adhesion.

Cleanup Clean excess material with a damp cloth. Clean hands and tools with soap and water. Scrape dried excess.

Limitations

Titebond Painter's Caulk should be dry to the touch and ready to paint in 2-4 hours. Dry time may be extended in humid or cold conditions. It is not designed for continuous submersion or use below the waterline. For questions, please call our toll free Help Line 1-800-347-4583 or visit us at titebond.com.

Caution Statements

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT. Contains acrylic polymer, limestone, titanium dioxide, ethylene glycol and mineral derivatives. Harmful if swallowed. Long term exposure to ingredients in this product can increase the risk of certain cancers. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ordering Information

Part No.	Size	Weight	UPC	Case UPC	Units Per Package	Packages Per Pallet
7301	10.1 Oz. Cartridge - White	15.01	037083073010	10037083073017	12	108

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207
CUSTOMER SERVICE 1-800-669-4583
TECH SERVICE 1-800-347-4583
www.titebond.com

Franklin International