

PoroCELL

Closed-cell foam rubber sheets,
rolls and edging with or without
adhesive

“Mousse”





PoroceIl

Structure of material

Closed-cell foam rubber to make sheets, rolls and edging - also in self-extinguishing version
(NR-SBR/EPDM/CR/NBR-PVC/EVA-EPDM-METALLOCEN).

Use

Thermal insulation and soundproofing, wet-seal and gas-seal for doors, windows, ecc.
Antivibration, waterproofing.
Fields of use:
industry in general.

Density

From 60 kg/m³ to 350 kg/m³

Resistance to temperatures

From -40°C to +120°C

Standard Dimensions

Thickness from 1,5 mm to 60 mm
Jointed rolls 10/20/30 meters.
Sheet from 1000x2000 mm



Some edging and examples of water cuts done by Porocell



Some examples of milled products



Examples of some die-cut products



Porocell roll



EUROFOAM
EUROFOAM

Via Colombo 12
20020 LAINATE (MI) - Italy
Tel. 0039 02 93 79 66 60
Fax 0039 02 93 79 67 00
Internet: <http://www.eurofoam.com>
e-mail: info@eurofoam.com



Porocell Porocell Porocell

EPDM - CR - NBR/PVC

**Gomma espansa
a cellule chiuse**

Closed cells foam rubber



MOUSSE



EUROFOAM



www.eurofoam.com

Porocell

EPDM - CR - NBR/PVC

Struttura del materiale

- Gomma espansa a cellule chiuse in lastre, rotoli e profili anche in versione autoestinguente (UL 94 HF1-VO). Su richiesta lastre accoppiate a tessuto (uso ortopedico/sport).

Caratteristiche tecniche

- Colore: bianco, grigio, nero
- Densità: da 60 Kg/m³ a 350 Kg/m³
- Resistenza alla temperatura: da -40°C a +120°C

Dimensioni standard

- Lastre: mm 1000x2000
- Rotoli: mm 1000x10/20/30 mt.
- Spessore: da 1,5mm a 70mm
- Guarnizioni fustellate, fresate o tagliate ad acqua
- Profili con o senza adesivo

Applicazioni

- Isolamento termico e acustico, antivibrante e impermeabile; guarnizioni in genere.

Structure of material

- Closed-cell foam rubber sheets, rolls and edging self-extinguishing (UL94 HF1-VO). Upon request sheets coupled with cloth (orthopaedic applications/sport).

Technical characteristics

- Colour: white, grey, black
- Density: from 60 Kg/m³ to 350 Kg/m³
- Temperature resistance: from -40°C to +120°C

Standard sizes

- Sheets: mm 1000x2000
- Rolls: mm 1000x10/20/30mt.
- Thickness: from 1,5mm to 70mm
- Gaskets made with punching, milling or water-jet system
- Edging with or without adhesive

Application

- Thermal insulation and soundproofing, antivibration and waterproofing; different types of gaskets.



EUROFOAM

via C. Colombo, 12 - 20020 Lainate (MI) Italy

Tel. ++39+2 93796660

Fax ++39+2 93796700

http://www.eurofoam.com

E-mail: info@eurofoam.com



EUROFOAM

è una Azienda certificata

UNI EN ISO 9001