

DECLARATION OF PERFORMANCE (DoP: SEC-001)**Construction Products Regulation (EU) No 305/2011**

- | | |
|----------------------------------|---|
| 1. Product Type: | HERTALAN® EASY STICK GS |
| 2. Intended use: | Damp proof and basement tanking sheets, EN 13967 |
| 3. Contact data producer: | Carlisle Construction Materials bv
Industrieweg 16
NL 8263 AD Kampen |
| 4. Contact data distributor: | n.a. |
| 5. AVCP: | 2+ |
| 6a. Harmonised standard | EN 13967: 2012 |
| Notified body (hEN): | KIWA Nederland bv
Notified body no.: 0620 |
| 6b. European Assessment Document | n.a. |



7. Declared Performance			
Essential Characteristics	Performance	Test Standard	Harmonised technical standard
Reaction to fire	Class E	EN 13501-1	EN 13967: 2012
Watertightness	Pass	EN 1928	
Tear resistance (l/b) (N)	≥ 150	EN 12310-1	
Joint shear resistance (N/50 mm)	≥ 250	EN 12317-2	
Impact resistance (mm)	Npd	EN 12691	
Tensile strength (l/b) (N/mm ²)	≥ 6	EN 12311-2B	
Elongation (l/b) (%)	≥ 400	EN 12311-2B	
Resistance to static load (kg)	npd	EN 12730	
Durability (artificial ageing)	Pass	EN 1296 / EN 1928	
Durability (alkali)	Pass	EN 1847 / EN 1928	
Dangerous substances	Meets requirements		

8. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Onno Fokkinga, manager R&D

Kampen, August 2016